

# Oculink (SFF-8612) & SATA to 2.5" U.2 SSD Adapter

## Features

- ※ U.2(SFF-8639) to SFF-8612 OCulink convert
- ※ SATA 2.5" form factor to 3.5" form factor convert
- ※ Build in SATA 7+15 pin connector
- ※ Build in SFF-8639 connector, pin-out defined by PCIe
- ※ Build in SFF-8612 connector, pin-out defined by PCIe
- ※ LED 1 Red LED on indicates SSD active status
- ※ LED 2 Green LED Blinking indicates SSD power ready
- ※ LED 3 Green LED Blinking indicates SSD power ready

## Specifications

- ※ Compliant with NVM Express 1.0a
- ※ Compliant with SATA Reversion 3.2
- ※ Support PCI Express Base Specification Rev 3.1
- ※ Support SSD\_Form\_Factor\_Version1\_a
- ※ Compliant with SFF-8639 Specification Rev 2.1
- ※ Compliant with PCIe OCULink Specification Rev 1.0

## Application

- ※ SFF-8611 to SFF-8611 Cable for SFF-8612 OCulink Host by SFF-9402 defined PCIe RefClk0 p,n
- ※ SFF-8654 to SFF-8611 Cable for SFF-8654 Slimline Host by SFF-9402 defined PCIe RefClk0 p,n
- ※ SFF-8643 to SFF-8611 Cable for SFF-8643(mini SAS HD) Host by INTEL defined PCIe RefClk0 p,n

