



MINERVA

PU407AH Converter Card

Performance & Burn In Test Rev. 1. 0

Table of Contents

1. Overview

2. Performance Measurement Tools and Results

2.1 Test Platform

2.2 Test target and use M.2 NVMe SSD

2.3 Install Hardware

2.4 BIOS & Windows 10 OS environment setup

2.5 CrystalDiskMark 5.2.1 x64 performance test

2.6 AS SSD Benchmark 1.9 performance test

2.7 ATTO Disk Benchamrk 2.47 performance test

2.8 AnvilBenchmark_V110_B337 Benchmark performance test

3. Burn In Tests and Results

3.1 BurnInTest v8.1 Pro burn in test

4. Summary

PU407A Converter Card

1. Overview


PU407A adapter, providing M.2 M-key connector can be M.2 (PCI-e I/F NVMe) SSD converted into U.2(SFF-8639), PCI-e Gen 3 / 4 Lanes interface and uses heat sink strip to M2 SSD.

2. Tools and Results of Performance Measurement

2.1 Test Platform

M/B : GIGABYTE **Z170X UD5 TH**
CPU : Intel **i5-6500**, 3.2GHz/ 6M Cache/ LGA1150
Memory : Kingston **KVR21N15D8/8**, **DDR4-2133MHz**, 8G(8GB DIMM*2)
ATX Power : FSP RAIDER 550, **550W ATX**, 12V V2.2 Power Supply
Graphic : Z170 Chipsets built-in **HD Graphics 530**
Adapter: PE0404 PCIe to SFF-8643 Mini SAS HD Adapter
CABLE: Amphenol U.2(SFF-8639) to SFF-8643 Mini SAS HD Cable
OS : Microsoft **Windows 10 64bit OS**

2.2 Test target: PU407AH adapter & Micron 7100 M.2 22110(NVMe)/800GB SSD



PU407AH + Heat Sink



Micron 7100 22110 NVMe SSD

2.3 Install Hardware

Insert M.2 SSD into PU407A converter's M.2 M-key connector, and then with coppers, and screws to fix SSDs. (Please refer to the Installation Notes). Connect PU407AH converter to PE0404 adapter(PCI-e 4-lane to Mini SAS HD SFF-86437) using U.2 cable, Plug PE0404 into **PCI-e slot of Z170X UD5 TH**.

2.4 BIOS & Windows 10 OS environment setup


2.4.1 Install Windows 10 64bit OS into PU407AH

PU407A Converter Card

2.5 CrystalDiskMark 5.2.1 x64 performance test

※Benchmark (Sequential **Read & Write** / default = **1MB**)


2.5.1 Show **M.2 22110(NVMe) Micron 7100/800GB** performance as below:



2.6 AS SSD Benchmark 1.9 performance test

※Benchmark (**Read & Write** by MB/s, default block size = **16MB**)


2.6.1 Show **M.2 22110(NVMe) Micron 7100/800GB** performance as below:



PU407A Converter Card


2.7 ATTO Disk Benchmark 2.47 performance test

2.7.1 Show **M.2 22110(NVMe) Micron 7100/800GB** performance as below:



2.8 AnvilBenchmark_V110_B337

2.8.1 Show **M.2 22110(NVMe) Micron 7100/800GB** performance as below:





PU407A Converter Card

3. Burn In Tests and Results


3.1 BurnInTest v8.1 Pro for **M.2 22110(NVMe)** **Micron 7100/800GB SSD**

3.3.1 system information as below:




PU407A Converter Card

3.1.2 show Disk test mode(10 ways cycle test)



3.1.3 show 24-hour Burn-in test PASSED



PU407A Converter Card

4. Summary

- 4.1 M.2 SSD is PCI-e Gen 3 / 4 Lanes Interface, I/O speed, max. to 4GB.
- 4.2 PU407AH adapter I/O performance is based on M.2 NVMe PCI-e Gen 3 / 4 Lanes SSD.