



U.2 (SFF-8639) male to M.2 NVMe SSD Adapter



Features

- ※ M.2 NVMe to U.2 (SFF-8639) converter
- ※ Built-in M.2 M-key Female connector
- ※ Built-in SFF-8639 connector, pin-out defined by PCI Express
- ※ PWM synchronous buck converter Power IC
 - 4A maximum output current
 - Short circuit protection
 - In-rush current suppression
 - Thermal shutdown protection
 - ESD HBM (Human Body Mode)/2KV
- ※ Support 3.3V CLKREQ#
- ※ Supports 1.8V SMB_CLK
- ※ Supports 1.8V SMB_DATA
- ※ D1 Green LED on indicates M.2 NVMe SSD power ready
- ※ D2 RED LED Blinking indicates M.2 NVMe SSD active status

Specifications

- ※ Compliant with NVM Express 1.0a
- ※ Support PCI Express Base Specification Rev 3.0
- ※ Support SSD_Form_Factor_Version 1_a
- ※ Compliant with PCI Express M.2 Specification Version 1.0
- ※ Compliant with SFF-8639 Specification Rev 2.0

2.5" SSD Form Factor Support :

- ※ Type 2230-D2-B-M : 30mm (L) x 22mm (W)
- ※ Type 2242-D2-B-M : 42mm (L) x 22mm (W)
- ※ Type 2260-D2-B-M : 60mm (L) x 22mm (W)
- ※ Type 2280-D2-B-M : 80mm (L) x 22mm (W)
- ※ Type 22110-D2-B-M : 110mm (L) x 22mm (W)