

U.2 & SATA 7-pin to 2.5" U.2 SSD & M.2 SATA SSD

Features

- ※ Build in U.2(SFF-8639) Female connector
- ※ Supports U.2 SMB_CLK
- ※ Supports U.2 SMB_DATA
- ※ Supports U.2 Dual port design
- ※ Supports SAS Primary port design
- ※ Support 2.5" U.2 NVMe SSD, M.2 B-key
- ※ D1 Green LED on indicates M.2 SSD power ready
- ※ D2 Green LED on indicates U.2 SSD power ready
- ※ D4 RED LED Blinking indicates U.2 SSD active status
- ※ D5 RED LED Blinking indicates M.2 SSD active status

Specifications

- ※ Compliant with NVM Express 1.0a
- ※ Support PCI Express Base Specification Rev 3.0
- ※ Support SSD_Form_Factor_Version1_a
- ※ Compliant with SFF-8639 Specification Rev 2.0
- ※ Compliant with SFF-8323 Rev1.6
For 3.5" Form Factor Drive with Serial Attached Connector
- ※ Compliant with SerialATA_Revision_3_2_Gold

M.2 SSD / M.3 SSD Form Factor Support :

- ※ Type 2242-D2-B-M: 42mm(L) x 22mm(W)
- ※ Type 2260-D2-B-M: 60mm(L) x 22mm(W)
- ※ Type 2280-D2-B-M: 80mm(L) x 22mm(W)
- ※ Type 22110-D2-B-M: 110mm(L) x 22mm(W)
- ※ Type 305110: 110mm(L) x 30.5mm(W) HD

